

**VOLTAGE RANGE: 12 KV**  
**CURRENT: 5.0 mA**

### Features


- High speed switching
- High Current
- High surge resistivity for CRT discharge
- High reliability design
- High Voltage

### Mechanical Data

- X light Power supply
- Laser
- Voltage doubler circuit
- Microwave emission power



### Outline Drawings : mm



### Maximum Ratings and Electrical Characteristics $T_A = 25^\circ\text{C}$ unless otherwise specified

Characteristic	Symbols	ESJA52-12A		Units
Repetitive Peak Reverse Voltage	$V_{RRM}$	12		kV
Average Output Current $T_A=25^\circ\text{C}$ , Resistive Load	$I_o$	5.0		mA
Surge Current	$I_{FSM}$	0.5		A
Maximum Forward Voltage Drop at $25^\circ\text{C}$ , $I_F = I_{F(AV)}$	$V_F$	35		V
Maximum Reverse Current	$V_{RRM}$	2.0		uA
at $25^\circ\text{C}$		5.0		uA
at $100^\circ\text{C}$				
Maximum Reverse Recovery Time at $25^\circ\text{C}$	$T_{rr}$	80		nS
Junction Capacitance at $25^\circ\text{C}$ , $V_R=0\text{V}$ , $f=1\text{MHz}$	$C_j$	2.0		pF
Junction Temperature	$T_j$	125		$^\circ\text{C}$
Allowable Operation Case Temperature	$T_c$	125		$^\circ\text{C}$
Storage Temperature	$T_{stg}$	-40 to +125		$^\circ\text{C}$