

**VOLTAGE RANGE: 20 - 100V**  
**CURRENT: 2.0 A**


### Features

- Schottky Barrier Chip
- Ideally Suited for Automatic Assembly
- Low Power Loss, High Efficiency
- For Use in Low Voltage Application
- Guard Ring Die Construction
- Plastic Case Material has UL Flammability Classification Rating 94V-O



### Mechanical Data

- Case: SMB/DO-214AA, Molded Plastic
- Terminals: Solder Plated, Solderable per MIL-STD-750, Method 2026
- Polarity: Cathode Band or Cathode Notch
- Marking: Type Number
- Weight: 0.093 grams (approx.)



SMB(DO-214AA)		
Dim	Min	Max
A	3.30	3.94
B	4.06	4.70
C	1.91	2.21
D	0.15	0.31
E	5.00	5.59
G	0.10	0.20
H	0.76	1.52
J	2.00	2.62
All Dimensions in mm		

### Maximum Ratings and Electrical Characteristics T<sub>A</sub> = 25°C unless otherwise specified

Single phase, half wave, 60Hz, resistive or inductive load. For capacitive load, derate current by 20%.

Characteristic	Symbol	SK22	SK23	SK24	SK25	SK26	SK28	SK210	Unit
Maximum repetitive peak reverse voltage	V <sub>RRM</sub>	20	30	40	50	60	80	100	V
Maximum RMS voltage	V <sub>RMS</sub>	14	21	28	35	42	56	70	V
Maximum DC blocking voltage	V <sub>DC</sub>	20	30	40	50	60	80	100	V
Maximum average forward rectified current at T <sub>L</sub> (see fig.1)	I <sub>(AV)</sub>	2.0							A
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	I <sub>FSM</sub>	50.0							A
Maximum instantaneous forward voltage at 2.0A	V <sub>F</sub>	0.55		0.70		0.85		V	
Maximum DC reverse current at rated DC blocking voltage <small>T<sub>A</sub>=25°C</small> <small>T<sub>A</sub>=100°C</small>	I <sub>R</sub>	0.5			10			mA	
Typical junction capacitance (NOTE 1)	C <sub>J</sub>	220			180			pF	
Typical thermal resistance (NOTE 2)	R <sub>θJA</sub>	75.0							°C/W
Operating junction temperature range	T <sub>J</sub>	-65 to +125			-65 to +150			°C	
Storage temperature range	T <sub>STG</sub>	-65 to +150							°C

**Note:**1. Measured at 1MHz and applied reverse voltage of 4.0V D.C.

2. P.C.B. mounted with 0.2x0.2" (5.0x5.0mm) copper pad areas

## RATINGS AND CHARACTERISTIC CURVES SK22 THRU SK210

